

# Tactile Ground Surface Indicators



## 316 Discrete Tactile Black PVD 18mm Pressure Fit

### Tactile Dimensions

<b>Square Metre Ratio</b>	400 studs per 1m <sup>2</sup>
---------------------------	-------------------------------

### Dome Dimensions

<b>Top of Dome</b>	25mm
<b>Bottom of Dome</b>	35mm
<b>Height of Dome</b>	5mm

<b>Range</b>	Guardian Discrete Tactile Ground Surface Indicator
<b>Material</b>	High Quality - 316 Marine Grade Stainless Steel With Black PVD Coating
<b>Substrates</b>	Concrete, Granite, Aggregate, Vinyl, Carpet Tiles
<b>Installation</b>	Plug & Tap Pressure Fitted Design
<b>Standards</b>	Complies with National Construction Code - Building Code of Australia D3.8 Manufactured to comply with Australian Standards AS/NZS 1428.4.1-2009 Manufactured to comply with Australian Standards AS/NZS 4586-2013
<b>Warranty</b>	<b>Guaranteed for 5 Years</b>

<b>Slip Resistant Testing</b>		
<b>AS/NZS 4586:2013</b>	OIL - WET Ramp Analysis	Class R12
<b>AS/NZS 4586:2013</b>	WET Pendulum Analysis	Class P5

<b>Guardian Colour and Stock Codes</b>				
<b>Colours</b>	<b>Application</b>	<b>Stem Width</b>	<b>Stem Length</b>	<b>Stock Codes</b>
Black	Internal and External	8.5mm plug	18mm plug	GTS818EP-PVDBK

<b>Luminance Contrast Requirements</b>	
The National Construction Code of Australia and the AS/NZS 1428.4.1 require a minimum luminance contrast.	
The luminance guidelines for TGSI's to contrast against the base surface is as follows:	
The raised section shall have a minimum contrast of 45% when constructed of one material/colour	

*Durable & UV Resistant, Versatile, Premium Quality*