

Premium Wheel Stops



| | |
|-------------|--|
| Range | Guardian Premium Wheel Stops |
| Design | Manufactured and supplied as one piece |
| Substrates | Concrete, Brick Paving, Bitumen |
| Standards | Australian Standards AS 2890.1-2004 |
| Warranty | Guaranteed for 1 Year |
| Application | Asphalt Spikes or Concrete Dynabolts |
| Dimensions | 1,650mm (l) x 159mm (w) x 100mm (h) |

| Wheel Stop Features | |
|--|--|
| UV Resistant, tested in Australia’s harsh conditions | |
| Light weight design (17.5kg) for one man installations | |
| Waterproof materials and only 3 fixings are required | |
| Economical, simple and easy to install | |

Guardian Colour and Stock Codes

| Colours | Application | Materials | Product Code |
|-------------------------|-----------------------|-----------------|----------------|
| Black (Yellow Chevrons) | Internal and External | Solid Rubber | GTSWS1650BK |
| Black (Blue Chevrons) | Internal and External | Solid Rubber | GWS-RB1650BKB |
| Grey | Internal and External | Moulded Plastic | GWS-MD1650GY |
| Yellow | Internal and External | Moulded Plastic | GWS-MD1650YL |
| Blue | Internal and External | Moulded Plastic | GTSWS-MD1650BL |

Moulded Plastic Design

These new wheel stops are moulded from a tough, UV stabilised polyethylene compound and are available in yellow, grey and blue (to highlight disabled parking bays).

