


*Lengths greater than 2.5m may have an additional cost

Guardian Stair Nosing



Heavy Duty Anodised Aluminium Profiles

Product	Aluminium Striped Strip 3x50mm
Material	Anodised Aluminium (Fixing heads will be visible if required)
Size	Cut-to-size up to 5m*
Substrates	Timber, Concrete, Tiles, Vinyl, Thin Carpet (Not suitable for carpet with underlay)
Standards	Manufactured to Australian Standards AS/NZS 1428.1 National Construction Code D2.13 and D2.14
Warranty	Guaranteed for 5 Years



Slip Resistant Testing

AS/NZS 4586:2013	WET Pendulum Analysis	Slip Resistance Value (SRV) = 41	Class P4
------------------	-----------------------	----------------------------------	----------

Guardian Colour and Stock Codes

Colours	Application	Striped Strip
Silver Anodised	Internal and External	GSN-02STS-SV
Gold Anodised	Internal and External	GSN-02STS-GD
Black Anodised	Internal and External	GSN-02STS-BK

Luminance Reflective Value

Colours	Mean Dry Luminance (LRV)	Mean Wet Luminance (LRV)
Silver Anodised	50.38	48.73
Black Anodised	3.33	3.31

Luminance Contrast Requirements

The National Construction Code of Australia and the AS/NSZ 1428.4.1 require a minimum luminance contrast.

The luminance contrast guideline for Stair Nosings to contrast against the base surface is as follows:

- The strip of contrasting colour shall have a minimum contrast of 30% against the substrate.
- The strip of contrasting colour shall be 50mm–75mm wide.

*Lengths greater than 2.5m may have an additional cost