



Concrete Tactile Warning Indicators

Tactile Dimensions

Tactile Thickness	40mm, 60mm
Gap between Centres	50mm
Square Metre Ratio (300mm x 300mm)	11 tiles per 1m ²
Square Metre Ratio (400mm x 400mm)	6.25 tiles per 1m ²

Dome Dimensions

Top of Dome	25mm
Bottom of Dome	35mm
Height of Dome	5mm

Range	Guardian Integrated Tactile Ground Surface Indicator
Material	Concrete
Substrates	Concrete, Granite, Aggregate, Tiles, Pavers
Installation	Designed to be recessed into substrate
Standards	Complies with National Construction Code - Building Code of Australia D3.8 Manufactured to Australian Standards AS/NZS 1428.4.1-2009 Complies to Australian Standards AS/NZS 1428.4.1-2009 Complies to Australian Standards AS/NZS 4586-2013
Warranty	5 Year Product Warranty

Guardian Colour and Stock Codes					
Colours	Application	Warning 300x300x40mm	Warning 300x300x60mm	Warning 400x400x40mm	Warning 400x400x60mm
Rough Charcoal	Internal and External	GTI-01CW-34RCH	GTI-01CW-36RCH	GTI-01CW-44RCH	GTI-01CW-46RCH
Rough Ivory	Internal and External	GTI-01CW-34RIV	GTI-01CW-36RIV	GTI-01CW-44RIV	GTI-01CW-46RIV
Rough Red	Internal and External	GTI-01CW-34RRD	GTI-01CW-36RRD	GTI-01CW-44RRD	GTI-01CW-46RRD
Rough Yellow	Internal and External	GTI-01CW-34RYL	GTI-01CW-36RYL	GTI-01CW-44RYL	GTI-01CW-46RYL
Smooth Charcoal	Internal and External	GTI-01CW-34SCH	GTI-01CW-36SCH	GTI-01CW-44SCH	GTI-01CW-46SCH
Smooth Ivory	Internal and External	GTI-01CW-34SIV	GTI-01CW-36SIV	GTI-01CW-44SIV	GTI-01CW-46SIV
Smooth Red	Internal and External	GTI-01CW-34SRD	GTI-01CW-36SRD	GTI-01CW-44SRD	GTI-01CW-46SRD
Smooth Yellow	Internal and External	GTI-01CW-34SYL	GTI-01CW-36SYL	GTI-01CW-44SYL	GTI-01CW-46SYL

Durable & UV Resistant, Versatile, Premium Quality