



## Solid 316 Stainless Steel Discrete Tactile Plug & Screw

### Tactile Dimensions

|                    |                               |
|--------------------|-------------------------------|
| Square Metre Ratio | 400 studs per 1m <sup>2</sup> |
|--------------------|-------------------------------|

### Dome Dimensions

|                |      |
|----------------|------|
| Top of Dome    | 25mm |
| Bottom of Dome | 35mm |
| Height of Dome | 5mm  |

|                     |  |
|---------------------|--|
| <b>Range</b>        | Guardian Discrete Tactile Ground Surface Indicator   |
| <b>Material</b>     | High Quality - 316 Marine Grade Stainless Steel with Screw & Plug  |
| <b>Substrates</b>   | Timber, Concrete, Vinyl, Carpet Tiles  |
| <b>Installation</b> | Screw & Plug Design  |
| <b>Standards</b>    | Complies with National Construction Code - Building Code of Australia D3.8<br>Manufactured to comply with Australian Standards AS/NZS 1428.4.1-2009<br>Manufactured to comply with Australian Standards AS/NZS 4586-2013 |
| <b>Warranty</b>     | <b>Guaranteed for 5 Years</b>  |

|                               |                         |           |
|-------------------------------|-------------------------|-----------|
| <b>Slip Resistant Testing</b> |                         |           |
| AS/NZS 4586:2013              | OIL - WET Ramp Analysis | Class R12 |
| AS/NZS 4586:2013              | WET Pendulum Analysis   | Class P5  |

|  |                       |                    |                     |                    |                    |
|--|-----------------------|--------------------|---------------------|--------------------|--------------------|
| <b>Guardian Colour and Stock Codes</b> |                       |                    |                     |                    |                    |
| <b>Colours</b>                         | <b>Application</b>    | <b>Screw Width</b> | <b>Screw Length</b> | <b>Plug Length</b> | <b>Stock Codes</b> |
| Stainless Steel                        | Internal and External | 4mm                | 22mm                | 32mm               | GTS425PS-316       |

|   |
|---|
| <b>Luminance Contrast Requirements</b>  |
| The National Construction Code of Australia and the AS/NZS 1428.4.1 require a minimum luminance contrast. |
| The luminance guidelines for TGSI's to contrast against the base surface is as follows:                   |
| The raised section shall have a minimum contrast of 45% when constructed of one material/colour           |

*Durable & UV Resistant, Versatile, Premium Quality*