

# Tactile Ground Surface Indicators



## Solid 316 Stainless Steel Discrete Tactile 18mm Pressure Fit

### Tactile Dimensions

Square Metre Ratio	400 studs per 1m <sup>2</sup>
--------------------	-------------------------------

### Dome Dimensions

Top of Dome	25mm
Bottom of Dome	35mm
Height of Dome	5mm

<b>Range</b>	Guardian Discrete Tactile Ground Surface Indicator
<b>Material</b>	High Quality - 316 Marine Grade Stainless Steel
<b>Substrates</b>	Concrete, Granite, Vinyl, Carpet Tiles
<b>Installation</b>	Plug & Tap Pressure Fitted Design
<b>Standards</b>	Complies with National Construction Code - Building Code of Australia D3.8 Manufactured to comply with Australian Standards AS/NZS 1428.4.1-2009 Manufactured to comply with Australian Standards AS/NZS 4586-2013
<b>Warranty</b>	<b>Guaranteed for 5 Years</b>

Slip Resistant Testing		
AS/NZS 4586:2013	OIL - WET Ramp Analysis	Class R12
AS/NZS 4586:2013	WET Pendulum Analysis	Class P5

Guardian Colour and Stock Codes				
Colours	Application	Stem Width	Stem Length	Stock Codes
Stainless Steel	Internal and External	8.5mm plug	18mm plug	GTS818P-316

Luminance Contrast Requirements
The National Construction Code of Australia and the AS/NZS 1428.4.1 require a minimum luminance contrast.
The luminance guidelines for TGSi's to contrast against the base surface is as follows:
The raised section shall have a minimum contrast of 45% when constructed of one material/colour

*Durable & UV Resistant, Versatile, Premium Quality*