

Tactile Ground Surface Indicators



Solid 316 Stainless Steel Discrete Tactile 30mm Pressure Fit

Tactile Dimensions

Square Metre Ratio	400 studs per 1m ²
--------------------	-------------------------------

Dome Dimensions

Top of Dome	25mm
Bottom of Dome	35mm
Height of Dome	5mm

Range	Guardian Discrete Tactile Ground Surface Indicator
Material	High Quality - 316 Marine Grade Stainless Steel
Substrates	Concrete, Granite, Vinyl, Carpet Tiles
Installation	Plug & Tap Pressure-Fitted Design
Standards	Complies with National Construction Code - Building Code of Australia D3.8 Manufactured to comply with Australian Standards AS/NZS 1428.4.1-2009 Manufactured to comply with Australian Standards AS/NZS 4586-2013
Warranty	Guaranteed for 5 Years

Slip Resistant Testing		
AS/NZS 4586:2013	OIL - WET Ramp Analysis	Class R12
AS/NZS 4586:2013	WET Pendulum Analysis	Class P5

Guardian Colour and Stock Codes				
Colours	Application	Stem Width	Stem Length	Stock Codes
Stainless Steel	Internal and External	8.5mm plug	30mm plug	GTS830P-316

Luminance Contrast Requirements
The National Construction Code of Australia and the AS/NZS 1428.4.1 require a minimum luminance contrast.
The luminance guidelines for TGSi's to contrast against the base surface is as follows:
The raised section shall have a minimum contrast of 45% when constructed of one material/colour

Durable & UV Resistant, Versatile, Premium Quality