

Tactile Ground Surface Indicators



Solid Brass Discrete Tactile - 15mm Stem

Tactile Dimensions

Square Metre Ratio	400 studs per 1m ²
---------------------------	-------------------------------

Dome Dimensions

Top of Dome	25mm
Bottom of Dome	35mm
Height of Dome	5mm

Range	Guardian Discrete Tactile Ground Surface Indicator
Material	High Grade Solid Brass
Substrates	Concrete, Granite, Aggregate, Tiles, Vinyl, Timber, Pavers
Installation	Epoxy Adhesive Fixed Design
Standards	Complies with National Construction Code - Building Code of Australia D3.8 Manufactured to comply with Australian Standards AS/NZS 1428.4.1-2009 Manufactured to comply with Australian Standards AS/NZS 4586-2013
Warranty	Guaranteed for 5 Years

Slip Resistant Testing		
AS/NZS 4586:2013	OIL - WET Ramp Analysis	Class R12
AS/NZS 4586:2013	WET Pendulum Analysis	Class P5

Guardian Colour and Stock Codes				
Colours	Application	Stem Width	Stem Length	Stock Codes
Brass	Internal and External	6mm	15mm	GTS615-BRS

Luminance Contrast Requirements	
The National Construction Code of Australia and the AS/NZS 1428.4.1 require a minimum luminance contrast.	
The luminance guidelines for TGSI's to contrast against the base surface is as follows:	
The raised section shall have a minimum contrast of 45% when constructed of one material/colour	

Durable & UV Resistant, Versatile, Premium Quality